

Via Italo Calvino 7 Lotto 1 - Edificio A13-14 20017 Rho (MI) Tel. +39 02 36569371 info@danetech.it www.danetech.it



# Additel 927 Hydraulic Pressure Test Pump

- Generate 85% vacuum to 10,000 psi (700 bar) pressure
- Portable, only 7 lb
- Minimal maintenance
- Increase and decrease pressure smoothly
- Hand-tight quick connectors



#### **OVERVIEW**

The 927 Hydraulic Pressure Test Pump is a hand operated pressure pump designed to generate pressure from 85% vacuum to 10,000 psi (700 bar). With the patented screw press technology, high pressures can be easily generated, as well as increased and decreased smoothly. With no check valve (non-returning valve), the 927 avoids the troublesome leakage issues that is usually experienced with most hand pumps and allows for minimal maintenance. Two hand-tight quick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 927 is an ideal comparison test pump for calibrating pressure measuring instruments such as test gauges, indicators or transducers in the field or laboratory.

### **FEATURES**

- PortableOnly 7 lb
- Durable and Minimal Maintenance
   Patented screw press technology, without non-returning valve inside that is usually used on
- troublesome hand pumps.

  Easy-to-use

The high pressure can be generated easily, as well as increased and decreased smoothly.

- Extremely Low Leakage
  - Patented screw press technology, replaces troublesome check valves (non-returning valve) used in most hand pumps which practically eliminates leakage.
- Hand-tight Quick Connectors
  Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches.


## **SPECIFICATIONS**

- Media: Oil or deionized water.
   (Oil is default media liquid. Pump with water as media to be ordered specifically)
- Reservoir capacity: 245 ml (15 in<sup>3</sup>)
- Generated Pressure Range 85% vacuum to 10,000 psi (700 bar) positive pressure.
- Material: Ram/adapters: SS
   Body: SS, aluminum
   Seals: Buna-N, PTFE, Copper Alloy
- Connection
  - Hand-tight connectors for both test gauge and reference gauge.
  - 1/4NPT female, 1/2NPT female, 1/4BSP female, 1/2BSP female, or M20X1.5 female
- **Dimensions:** Height: 5.31" (135 mm)
  Base: 11.42" (290 mm) x 7.80" (198 mm).
- Weight: 7 lb (3.2 kg).
- Warranty: 1 year
- Piston volume

Low pressure piston: 19 ml (1.2 in<sup>3</sup>) High pressure piston: 0.9 ml (0.05 in<sup>3</sup>)

# **ORDERING INFORMATION**

Model Number



Accessories included

Mineral oil,1 bottle (250 ml)\*

O-ring: 20 pcs Manual: 1 pc

\* When water media is not requested

#### Optional Accessories

Model number	Description
9202	Oil, Mineral Oil, 1 liter (1 quart)
ADT102	Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs). More information shown on page 61.
ADT103	Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs). More information shown on page 62.
ADT100-HTK	Hose test kit, 5 feet flexible hose, 15,000 psi, 1/4NPT male to 1/4NPT (1/8NPT, 1/2NPT, 1/4BSP,1/2BSP, or M20X1.5) female hand-tight quick connector. More information shown on page 63.
9904-927	Carrying Case for one 927 pump and two 681 gauges or 672 calibrators
ADT927-MK	Maintenance kit for Additel 927 pump