

9840 INTELLIGENT INDICATOR (U.S. & METRIC)

FEATURES & BENEFITS

- TEDS Plug & Play Ready IEEE 1451.4 compliant
- 1 or 2 channel
- Remote sense excitation
- 5 & 6 point linearization
- Bipolar
- ±999,999 display counts
- Nonlinearity < ±0.005%
- Auto setup for multiple load cells
- Fast, direct analog output
- ±10 VDC scalable analog output – 16 bit
- Full duplex RS232C communication
- Peak/valley hold with front panel reset
- Front panel and remote tare
- 8 selectable digital filters
- Auto zero
- Front panel shunt calibration with two selectable resistors
- Display units conversion: Lb, Kg, N, Psi, Mpa, Klb, kN, t, mV/V, lbf-in, oz-in, Nm
- Two-line display
- Quadrature encoder channel available
- mV/V calibration
- USB port

OPTIONS

- TEDS read/write template 33, 40, 41
- 2nd channel
- 2nd 16-bit scalable analog output
- Display Freeze/Remote Display Freeze
- 4-20 mA analog output
- Quad Limits
- RS485
- Multi-drop RS232
- Print Button
- 7-pin circular load cell connector
- Encoder Channel
- Second Line Enable on 1-channel unit
- Keylock

STANDARD CONFIGURATION



MODEL 9840-100-1-T (Shown)

SPECIFICATIONS

EXCITATION		
Voltage – VDC	5 or 10	
Current – MAX – mA	180	
OUTPUTS		
Serial Interface	RS232 duplex	
Output – Analog, 16 bit – VDC	Scalable, ±10	
Output – Analog, Direct – Hz	1.5K	
Output – Analog – mA	4–20 (optional)	
Limits	Quad-programmable	
PERFORMANCE		
Maximum Display Counts	±999,999	
Display Update / sec.	4	
Internal Resolution – bits	24	
Signal Input Range – mV/V	±4.5	
Programmable Count - by	1, 2, 5, 10, and 20	
Conversion Rate / sec.	60	
Maximum Error – %FS	0.01 ±1 count	
CMRR – dB	115	
ENVIRONMENTAL		
Operating Temperature	°F	+32 to +122
	°C	0 to +50
Storage Temperature	°F	+14 to +140
	°C	-10 to +60
Relative Humidity – % MAX	°F	95 (104) non-condensing
	°C	95 (40) non-condensing
POWER		
AC Power – VAC, Hz	115 or 230, 50–60	
DC Power (option)	Available as a special	
Power Consumption – watts	12	
MECHANICAL		
Dimensions - W x H x D	in	7.5 x 2.5 x 9.5
	mm	190.50 x 63.50 x 241.30
Weight	lbs	5
	kg	2.26796
Display	Vacuum Fluorescent	
Unit Annunciator	Lb, Kg, Klb, kN, N, mV/V, lbf-in, oz-in, Nm	

International System of Units (SI) dimensions and capacities are provided for conversion only. Standard products have U.S. capacities and dimensions. SI capacities available upon special request and at an additional cost.