Via Italo Calvino 7 Lotto 1 - Edificio A13-14 20017 Rho (MI) Tel. +39 02 36569371 info@danetech.it www.danetech.it



Short Probe Temperature Calibration Kit

- Reduce calibration uncertainties
- Avoid messy fluid baths
- Reduce calibration time
- Improved accuracy with custom control probe (included)
- Metric or Imperial kits available



OVERVIEW


The Additel 110 series short probe calibration kit is designed to help users of our ADT875-155 (-40°C dry well) calibrate temperature probes and transmitters with short probe lengths (4" or less). This all-inclusive kit comes with everything needed to perform more accurate and reliable calibration for those challenging short probes. Choose between our metric or imperial kit to fit your needs. Each kit comes complete with (3) standard sized inserts and (1) blank insert, which can be modified by the end user to accommodate custom sized UUT's if needed. The small reference probe is included which fits snuggly into the reference port of the specially machined inserts. Also, we include a small set of tools and supplies to help improve results by removing a couple of small parts on the top of the 875 calibrator. For more information, please watch our instructional short probe video found at www.additel.com

SPECIFICATIONS

AM1612-ADT Secondary	PRT Specifications	
Temperature Range	-40°C to 160 °C	
Resistance at 0 °C	Nominal 100 Ω	
Temperature Coefficient	0.00385 Ω/Ω /°C	
Accuracy	±0.05 °C at 0 °C	
Drift	$\pm 0.04~^{\circ}\text{C}$ at 0 $^{\circ}\text{C}$ after 100 hours at 160 $^{\circ}\text{C}$	
Short Term Stability	±0.02 °C	
Thermal Shock	±0.02 °C after 10 times thermal cycles from minimum to maximum temperatures	
Hysteresis	<= 0.01 °C	
Self-heating	75 mW/ °C	
Response Time	4 seconds for 63% response to step change in water moving at 3 feet per second	
Measurement Current	1 mA	
Sensor Length	30 mm	
Insulation Resistance	>1000 M Ω at room temperature	
Sheath Material	Stainless Steel 316 L	
Dimension	0.118 inch X 1.78 inch (3 mm X 45 mm)	
External Leads	Enameled copper wire protected by high temperature heat shrink tubing, 4 leads, 0.8 meters	
Calibration	NIST traceable calibration with data provided	

Optional Accessories


Model number	Description	Picture
ADT110-875-L-SK-Z	Spare Blank Insert	69 69
AM1612-ADT	Spare Short Style Secondary Reference Probe	Q



Short Probe Kit Application

ORDERING INFORMATION


Model Number



Type:

IKIT includes Imperial 1/8", 3/16", 1/4" inserts, (1) blank insert, reference probe and carrying case MKIT includes Metric 3, 4, 6 mm inserts, (1) blank insert, reference probe and carrying case

Note: Kits include (1) blank insert for field modification if needed



01